



LUMA 12 / 14

SCONCES WALL

location: **DAMP**

SPECIFICATIONS:

DESCRIPTION

Wall-mounted sconces featuring handcrafted glass. Two sizes available.

LAMPING

Standard: 60W A19 120V incandescent, suitable for dimming, lamp not included. *(Incandescent dimmer is suitable for dimming, not included)*

CFL: 4-Pin CFL with non-dimming electronic ballast. 120V, lamp not included.

GU24 CFL: Self-ballasted GU24 lampholders. 13W max, 120V, lamp not included.

LED: 9W LED Replaceable source 120V, dimmable, 80+ CRI, 3000°K CCT, 800 lumens, 30,000 hours, lamp included.

Consult factory for other CFL configurations., CFL lamps not included.

DIFFUSER

Diffuser shall be handcrafted glass of Opal Glossy decor.

Luma 12 #9095XX: 11.875" Dia. x 3.75" D

Luma 14 #9096XX: 14.375" Dia. x 4" D

CONSTRUCTION

Glass diffuser is secured to fitter with "twist & lock" bayonet action. Stamped aluminum fitter is powder coated white.

MOUNTING

Installs directly to a 4" octagonal outlet box, centered on fixture.

75°C supply wire required for incandescent lamping.


LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).




LUMA SHOWN IN OPAL GLOSSY/CLEAR

Luma 12: #9095



Luma 14: #9096



FIXTURE/DECOR	LAMP OPTIONS	OPTIONS
909539 Opal Glossy/Clear	(blank) 1x 60W A19 Incan D1 1x 13W Quad 120V GU24 1x 13W GU24 120V LED 1x 9W LED 120V, dimmable	LW Low Wattage labeling

FIXTURE/DECOR	LAMP OPTIONS	OPTIONS
909639 Opal Glossy/Clear	(blank) 2x 60W A19 Incan D2 2x 13W Quad 120V GU24 2x 13W GU24 120V LED 2x 9W LED 120V, dimmable	LW Low Wattage labeling

Ex. 909639

Luma 14 Slim Wall Sconce w/ Opal Glossy/Clear Glass

Project Information:

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.