

WAVE 12

FLUSH MOUNT CEILING

location:

SPECIFICATIONS:

DESCRIPTION

Flush-mounted ceiling luminaires, featuring handcrafted glass. Two sizes available.

LAMPING

Standard: 100W MAX E26 base A19, 120V, lamp not included. Dimmable with standard incandescent dimmer (not included).

LED Filament: 8W Replaceable LED Filament lamp, 120V, CL dimmable, 80+CRI, 3000°K CCT, 800 lumens, 25,000 hours, lamp included.

DIFFUSER

Handcrafted glass diffuser is available in various decors. 1.75" Dia. x 6.25" H

CONSTRUCTION

Glass diffuser is secured to fitter with "twist & lock" bayonet action. Stamped aluminum fitter.

MOUNTING

Installs directly to a 4" octagonal outlet box, centered on fixture. 90°C supply wire required for incandescent lamping.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).






WAVE 12 CEILING SHOWN IN CLEAR (906261C)

SMORE

Wave 12: #9062



FIXTURE/DECOR	- LAMP OPTIONS	- OPTIONS
906261C 11.75" Dia. Clear	(blank) 1x 100W A19	LW Low Wattage
906202C 11.75" Dia. Smoke	EDIL 1x 8W LED Filament	labeling

Project In	formation:		

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/24