

LINK

120V PENDANTS

location:

SPECIFICATIONS:

DESCRIPTION

For those that prefer strong geometric lines to curves, the Link's combination of beautiful hand blown clear outer glass encapsulating an etched matte opal inner glass will brighten any space.

LAMPING

Standard: 40W T10 Medium-based 120V, lamp not included. Dimmable with standard incandescent dimmer (not included).

LED: 9W Replaceable LED Lamp 120V, CL dimmable, 90+ CRI, 3000°K CCT, 800 lumens, 30,000 hours, lamp included. (Standard CCT is 3000K, 3500K and 4000K are also available)

DIFFUSER

Outer shade shall be of glass in various decors with an inner Opal cylinder glass shade. 8" Dia. x 10.5" H

SUSPENSION

Cord-hung: 10' SVT-type cord, complete with 5" decorative sleeve at the socketholder. Jacket coordinates with metal finish. Plated stamped steel construction. Black, Bronze or Satin Nickel. See next page for mulit light options.


Stem-mount: Includes 4 connectable stem sections (3", 6", 12" and 18" lengths) plus telescoping piece for up to 3" adjustment, 10' max. 5" Dia. canopy (with swivel) and stem sections are plated steel. Black, Bronze or Satin Nickel. *Additional Stem Sections can be ordered under accessories.

MOUNTING

Installs directly to a 4" octagonal ceiling box. Suitable for sloped ceilings.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only). Consult factory concerning lower wattage labeling for energy requirements.







Project Information:

For ordering information, see next page

All dimensions provided are nominal.


Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 7/23

ORDERING:

CONNECTION	- GLASS OPTIONS	- LAMP OPTIONS	- METAL FINISH -	OPTIONS
Cord Fixtures 1JC 1 Lt. Dome	LINKBL Blue/Opal LINKCL Clear/Opal	(blank) 40W T10 LED 3000K LED		L 15'Cord LW Lower
1JT 1 Lt. Flat	LINKSM Smoke/Opal	LED35 3500K LED		Wattage
		LED40 4000K LED		Labeling


Stem Fixture 1TT 1 Lt. Flat



Ex. 1JT-LINKCL-SN Link Pendant, Clear/Opal Shade, Satin Nickel Finish

PENDANT OPTIONS:

1JC/J CORD-HUNG PENDANT



- Flat (1JT) or Dome (1JC) Canopy styles. Dome style allows adjustment without cutting cord.
- "J" option is pendant less canopy for multiport canopy (options to the right)
- Suitable for sloped ceilings
- Cord: 10' SVT, 5" sleeve at socketholder
- Also available in 15⁶
- · Black, Bronze or Satin Nickel
- · Cord Sleeves are available in 18" lengths

1TT STEM PENDANT



- Swivel at canopy, suitable for sloped ceilings
- Includes telescoping section plus 4 connectable stem sections, (1x 3", 1x 6", 1x 12", 1x 18"), 10' max
- · Black, Bronze or Satin Nickel
- · Additional Stem Sections can be ordered under Accessories

ACCESSORIES:

ADDITIONAL STEM SECTIONS:

Additional connecting stems are available to increase overall length of a Stem Pendant, up to 10' max. Telescoping adjustable section allows up to 3" movement.

T20A-SN, BK or BR Adi. Section T203-SN, BK or BR 3" Section T206-SN, BK or BR 6" Section T212-SN, BK or BR 12" Section T218-SN, BK or BR 18" Section

LONGER CORD LENGTHS:

Longer cord length of 15' available. Add an " \boldsymbol{L} " to the end of the item number, i.e. 1JC-169707-SN-L.

LOW WATTAGE LABELING:

Incandescent fixture supplied with 16 watt relamp label.

Add an "LW" to the end of the item number, i.e. 1JC-169707-SN-LW.

CORD SLEEVES:

If concealing the cord is desired on a Cord-hung Pendant, order our 0.25" dia. metal sleeves. Each sleeve is 18" long and may be field cut.

T118-BK Black T118-BR Bronze T118-SN Satin Nickel

STEMHOOKS:

Suspension hooks allow cord drops to be placed wherever desired. Suitable for sloped ceilings or for greater multilight spacing

T103BK Black T103BR **Bronze** T103SN Satin Nickel


MULTIPORT CANOPY OPTIONS FOR CORD PENDANTS

T33X 3 LIGHT ROUND CANOPY

1.25"

- Suitable for sloped ceilings
- · Black, Bronze or Satin Nickel
- 10" Dia. shades MAX, with staggered heights
- * For larger diameter glasses, Stemhooks are required for spacing

T33XL 3 LIGHT LARGE ROUND CANOPY



- Suitable for sloped ceilings
- · Black, Bronze or Satin Nickel
- · 16" Dia. shades MAX, with staggered heights
- For larger diameter glasses, Stemhooks are required for spacing

T36X 6 LIGHT ROUND CANOPY

1.25" Suitable for sloped


 \bigcirc





* For larger diameter glasses, Stemhooks are required for

T39X 9 LIGHT ROUND CANOPY




- Suitable for sloped ceilings
- Black, Bronze or Satin Nickel
- 10" Dia. shades MAX, with staggered heights
- * For larger diameter glasses, Stemhooks are required for spacing

T33V 3 LIGHT BAR CANOPY




- · Suitable for sloped ceilings
- · Black, Bronze or Satin Nickel
- 20" Dia. shades MAX, with staggered heights
- * For larger diameter glasses, Stemhooks are required for spacing

T34V 4 LIGHT BAR CANOPY



- · Suitable for sloped ceilings
- · Black, Bronze or Satin Nickel
- 20" Dia. shades MAX, with staggered heights
- * For larger diameter glasses, Stemhooks are required for spacing

T37V 7 LIGHT BAR CANOPY



- · Suitable for sloped ceilings
- Black, Bronze or Satin Nickel
- 20" Dia, shades MAX, with staggered heights
- * For larger diameter glasses, Stemhooks are required for spacing

HOW TO ORDER A MULTILIGHT FIXTURE

Order your canopy with the selected 120V multi light pendants (indicated by "B" or "J" prefix) for the complete fixture:

Example: 1x T33X-SN (3 Light Round Canopy)

1x J-LINKCL-SN (Link Pendant in Clear/Opal)

1x J-LINKCL-SN (Link Pendant in Clear/Opal)

1x J-LINKCL-SN (Link Pendant in Clear/Opal)