# MOJO

12V SPOTLIGHTS

location DRY

## **SPECIFICATIONS:**

### **DESCRIPTION**

Low voltage spotlight with handcrafted glass. Includes Quick-Connect jack.

## **LAMPING**

Standard: 50W MAX GU5.3 base MR16 lamp, included.

**LED:** 9W Replaceable 12V LED MR16 Flood, dimmable, 90+ CRI, 3000°K CCT, 670 lumens, 25,000 hours, lamp included.

## **QUICK-CONNECT JACK**

Integral Quick-Connect jack is compatible with Besa Rail Adapter.

### **ELEMENT OPTIONS**


Available as either a Quick-Connect element only or with Rail Adapter for use with Besa Monorail. Longer stem options are also available.

#### **METAL FINISH**

Available in Black or Satin Nickel.

#### **LABELS**

UL or ETL Listed. Suitable for Dry Locations (interior use only).





MOJO IN BLACK & SATIN NICKEL W/ LED OPTION

## **SPOTLIGHT OPTIONS:**

# **SP** SPOTLIGHT ELEMENT ONLY



- Spotlight Fixture with Shade
- Quick-Connect Jack integral
- Compatible with Besa Canopies and Rail Adapter

# **RSP** SPOTLIGHT + RAIL ADAPTER



### READY FOR RAIL

- Spotlight Fixture with Shade, plus Rail Adapter
- Quick-Connect Jack integral
- Compatible with Besa Monorail System

# **ORDERING:**

QUICK-CONNECT	- SHADE OPTIONS -	LAMP OPTIONS	- STEM OPTIONS	- METAL FINISH
SP Jack Only	MOJOBK Metal Black	(blank) Bipin Socket	(blank) Standard	BK Black
RSP Rail-Ready	MOJOMN Metal Nickel	LED 9W LED MR16,	<b>06</b> 6"	SN Satin Nickel
		dimmable	<b>12</b> 12"	
			<b>18</b> 18"	

## Ex. SP-MOJOMN-SN

Mojo Spotlight w/ Metal Nickel Metal Shade, Satin Nickel Finish

Project Information:					

# **Longer Stem Options**


Besa spotlights have a standard stem 1.5" long. For a spotlight with a longer drop, order a stem length of 6", 12" or 18".

Not suitable for use on sloped ceiling when spotlight is installed on a quick-connect canopy.

Note: These are NOT field installable.
The complete unit is built at the factory.

Available options are

SP06 6" stem adds 3.625" to overall length
SP12 12" stem adds 9.625" to overall length
SP18 18" stem adds 15.625" to overall length



All dimensions provided are nominal.

Allowance must be made for dimensional tolerance in handcrafted glasses.

**REV 10/24**