

## B O B B I 10 / 12

FLUSH MOUNT CELLING

location:

## **SPECIFICATIONS:**

#### **DESCRIPTION**

Flush-mounted round ceiling luminaires, featuring handcrafted glass.

#### LAMPING

**Standard:** 60W A19 120V incandescent, lamp not included. Dimmable with standard incandescent dimmer (not included).

**LED:** 15W Integrated source, 120V, CL dimmable, 90+ CRI, 3000°K CCT, 1500 lumens, 50,000 hours, included. (For Bobbi 10 only)

**LED:** 20W Integrated source, 120V, CL dimmable, 90+ CRI, 3000°K CCT, 2000 lumens, 50,000 hours, included. (For Bobbi 12 only)

### **DIFFUSER**

Handcrafted glass diffuser is available in Marble decor.

**Bobbi 10 #9111:** 10" Dia. x 4.25" H **Bobbi 12 #9110:** 12" Dia. x 5.25" H

### **CONSTRUCTION**

Glass diffuser is secured to fitter with three set screws. Stamped aluminum fitter is powder coated white.

### **MOUNTING**

Installs directly to a 4" octagonal outlet box, centered on fixture. 90°C supply wire required for incandescent lamping.

### **LABELS**

UL or ETL Listed. Suitable for Damp Locations (interior use only).




BOBBI CEILING SHOWN IN OPAL CUT

# Bobbi 10: #9111 10" 4.25"

FIXTURE/DECOR	LAMP OPTIONS	- OPTIONS
<b>911152C</b> 10.0" Dia. Marble	(blank) 1x 60W A19 Incar	n <b>LW</b> Low
<b>911110C</b> 10.0" Dia. Opal Cut	LED 15W LED,	Wattage
	1500 lumens	labeling





FIXTURE/DECOR	-	LAMP OPTIONS		- OPTIONS	
911052C 12.0" Dia. Marble		(blank)	2x 60W A19 Incan	LW	Low
<b>911010C</b> 12.0" Dia. Opal Cut		LED	20W LED, 2000 lumens		Wattage labeling

### Ex. 911052C Bobbi 12 Ceiling w/ Marble Glass Shade

Project Information:
Project information.

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

**REV 10/24**