

KAILEE





location: DAMP

SPECIFICATIONS:

DESCRIPTION

Wall-mounted **ADA-compliant** sconce featuring open-top handcrafted glass.

Standard: 60W E12 base, 120V, suitable for dimming. lamp not included. (Incandescent dimmer is suitable for dimming, not included)

LED: 8W LED Replaceable source 120V, CL dimmable, 90+ CRI, 3000°K CCT, 800 lumens, 30,000 hours, lamp included.

DIFFUSER

Diffuser shall be handcrafted glass of various decors.

CONSTRUCTION

Glass is secured to the backplate by braided wire. Rectangular backplate (nominal 6.5" W x 4" H) shall be constructed of steel, powder-coated white.

METAL FINISH


Decorative metal accents shall be in various finish options.

MOUNTING

Installs directly to a 4" octagonal outlet box. 75°C supply wire required for incandescent lamping. Top of glass is approximately 3.75" above the outlet box centerline.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).





KAILEE SHOWN IN CARRERA (701719) & OPAL MATTE (701707)

ORDERING:

| FIXTURE/DECOR | - LAMP OPTIONS | - METAL FINISH | - OPTIONS |
|--------------------------|-------------------------|--------------------|-----------|
| 701707 Opal Matte | (blank) 60W E12 | BK Black | LW Low |
| 701719 Carrera | LED 8W LED 120V, | BR Bronze | Wattage |
| | dimmable | PN Polished Nickel | Labeling |
| | | SN Satin Nickel | |
| | | WH White | |

Ex. 701719-SN

Kailee Wall Sconce w/ Carrera Glass, Satin Nickel Finish

| Project Information: | | |
|----------------------|--|--|
| | | |
| | | |
| | | |
| | | |

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/24