



BRIO 14

120V PENDANTS

location:
DAMP

SPECIFICATIONS:

DESCRIPTION

The Brio 14 is a wide yet compact handcrafted European glass, softly radiused to fit gracefully into contemporary spaces.

LAMPING

Standard: 75W A19 120V incandescent, lamp not included. Dimmable with standard incandescent dimmer (not included).

LED: 9W Replaceable source, 120V, dimmable, 90+ CRI, 3000°K CCT, 800 lumens, 30,000 hours. Lamp included. (Standard CCT is 3000K, 3500K and 4000K are also available)

DIFFUSER

Shade shall be handcrafted glass of various decors. 13.75" Dia. x 6.875" H

Opening sizes: 42mm top.

SUSPENSION

Cord-hung: 10' SVT-type cord, complete with 5" decorative sleeve at the socketholder. Jacket coordinates with metal finish. Plated stamped steel construction. Black, Bronze or Satin Nickel. See next page for multi light options.

**For mounting to track, choose our "multi-light" connection option and select pendant track adapter seperately.*

Cable-hung: 1x 10' aircraft-quality stainless steel cable support with 10' AWM-type cord. Jacket coordinates with metal finish. 5" Dia. dome canopy is plated stamped steel. Black, Bronze or Satin Nickel.

Stem-mount: Includes 4 connectable stem sections (3", 6", 12" and 18" lengths) plus telescoping piece for up to 3" adjustment, 10' max. 5" Dia. canopy (with swivel) and stem sections are plated steel. Black, Bronze or Satin Nickel.

**Additional Stem Sections can be ordered under accessories.*

MOUNTING

Installs directly to a 4" octagonal or round ceiling box. Suitable for sloped ceilings.


LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).

Consult factory concerning lower wattage labeling for energy requirements.



BRIO 14 SHOWN IN SILVER FOIL (4345SF) WITH STEM PENDANT



Project Information:

For ordering information, see next page

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

Pendant Track Adapter

- Adapter connects Cord-hung Besa pendants to 120V track systems
- Black or White finish

Ordering:

B5450-H-BK/WH - Black or White
B5450-J-BK/WH - Black or White
B5450-L-BK/WH - Black or White






ORDERING:

CONNECTION	SHADE OPTIONS	LAMP OPTIONS	METAL FINISH	OPTIONS
Cord Fixture	4345GF Gold Foil	(blank) 75W A19 120V	BK Black	L 15' cord
1JC 1 Lt. Dome	4345SF Silver Foil	LED* 9W LED 120V, dimmable	BR Bronze	LW Low wattage labeling
1JT 1 Lt. Flat			SN Satin Nickel	

Cable Fixture
1KX 1 Lt. Dome

Stem Fixture
1TT 1 Lt. Flat

Multi light Cord Fixture
J For Multi light Canopy




Multilight Canopies Available, see right

*CCT options available (contact factory)


Ex. 1JT-4345GF-SN
Brio 14 Pendant w/ Gold Foil Glass, Satin Nickel Finish, Flat Canopy

MULTIPOINT CANOPY OPTIONS FOR CORD PENDANTS


T33X 3 LIGHT ROUND CANOPY




T33XL 3 LIGHT LARGE ROUND CANOPY




T36X 6 LIGHT ROUND CANOPY




T39X 9 LIGHT ROUND CANOPY




T38S 8 LIGHT SQUARE CANOPY




T33V 3 LIGHT BAR CANOPY



T34V 4 LIGHT BAR CANOPY



T37V 7 LIGHT BAR CANOPY



HOW TO ORDER A MULTILIGHT FIXTURE

Order your canopy with the selected 120V multi light pendants (indicated by "B" or "J" prefix) for the complete fixture:

Example: 1x T33X-SN (3 Light Round Canopy)


1x J-4345SF-SN (Brio 14 Pendant in Silver Foil)

1x J-4345SF-SN (Brio 14 Pendant in Silver Foil)


1x J-4345SF-SN (Brio 14 Pendant in Silver Foil)

PENDANT OPTIONS:


1JT / 1JC / J CORD-HUNG PENDANT



1TT STEM PENDANT



1KX CABLE-HUNG PENDANT



ACCESSORIES:

ADDITIONAL STEM SECTIONS:

Additional connecting stems are available to increase overall length of a Stem Pendant, up to 10' max. Telescoping adjustable section allows up to 3" movement.

T20A-SN, BK or BR	Adj. Section
T203-SN, BK or BR	3" Section
T206-SN, BK or BR	6" Section
T212-SN, BK or BR	12" Section
T218-SN, BK or BR	18" Section

LONGER CORD LENGTHS:

Longer cord length of 15' available. Add an "L" to the end of the item number, i.e. 1JC-169707-SN-L.

LOW WATTAGE LABELING:

Incandescent fixture supplied with 16 watt relamp label. Add an "LW" to the end of the item number, i.e. 1JC-169707-SN-LW.

CORD SLEEVES:

If concealing the cord is desired on a Cord-hung Pendant, order our 0.25" dia. metal sleeves. Each sleeve is 18" long and may be field cut.

T118-BK	Black
T118-BR	Bronze
T118-SN	Satin Nickel

STEMHOOKS:

Suspension hooks allow cord drops to be placed wherever desired. Suitable for sloped ceilings or for greater multilight spacing

T103BK	Black
T103BR	Bronze
T103SN	Satin Nickel