

location:
WET

SPECIFICATIONS:

DESCRIPTION

Semi-flush mount ceiling luminaire that features handcrafted glass.

LAMPING

Standard: 100W A19 120V, *lamp not included.*

LED Filament: : 8W Replaceable A19 LED Filament lamp, 120V, dimmable, 90+ CRI, 3000°K CCT, 800 lumens, 15,000 hours, lamp included.

DIFFUSER

The Billow 12 is a ceiling semi-flush design composed of a transparent glass diffuser, with an interesting bubble pattern blown randomly throughout the glass. 12" Dia. x 6.5" H

CONSTRUCTION

Glass diffuser is secured to fitter with "twist & lock" bayonet action. Stamped aluminum fitter.

MOUNTING

Installs directly to a 4" octagonal outlet box, centered on fixture. 90°C supply wire required for incandescent lamping.

LABELS


UL wet location when used under a covered ceiling.



8490SMC
Smoke Bubble



8490CLC
Clear Bubble



ORDERING:

8 | 4 | 9 | 0 | | C | - | | |

DECOR

CL Clear Bubble
SM Smoke Bubble

LAMPING

(Blank) 1x 75W A19 (Incan)
EDIL 1x 8W LED Filament

Project Information:

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 1/26