BESALIGHTING

BLINK

SCONCES OUTDOOR

location:
WET

SPECIFICATIONS:

DESCRIPTION
Wall-mounted sconces featuring handcrafted glass.

LAMPING
Standard: 60W T10 Medium-based 120V incandescent, lamp not included. Dimmable with standard incandescent dimmer (not included).
LED: 4W Replaceable 120V LED GU10, dimmable, 82+ CRI, 3000°K CCT, 240 lumens, 25,000 hours, lamp included.
LED Filament: 8W Replaceable T-shape LED Filament lamp, 120V, dimmable, 90+ CRI, 3000°K CCT, 800 lumens, 25,000 hours, lamp included.

DIFFUSER
Diffuser shall be handcrafted glass of various decors. 4.375" Dia. x 8" H

CONSTRUCTION
Cast Aluminum bracket powdered-coated in Black, Silver or White finish. Glass secured by set screws.

MOUNTING
Installs directly to a 4" octagonal outlet box. May be used in either upward or downward orientation in indoor applications, downward only for outdoor. 75°C supply wire required for incandescent lamping.

LABELS
UL or ETL Listed. Suitable for Wet Locations (interior or exterior use).

BLINK SHOWN IN BLUE/CLEAR (BLINKBL) & IN CLEAR (BLINKCL)



BLINKSM
SMOKE/CLEAR

ORDERING:

FIXTURE/DECOR		-	LAMP OPTIONS		-	METAL FINISH	
BLINKBL-WALL	Blue/Clear		**(blank)**	60W T10 Incan		**BK**	Black
BLINKCL-WALL	Clear		**EDIL**	8W LED Filament		**SL**	Silver
BLINKSM-WALL	Smoke/Clear		**LED**	4W LED		**WH**	White

Ex. BLINKSM-WALL-BK
Blink Sconce w/ Smoke/Clear Glass, Black Finish

Project Information:

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/24