

CAMINO

120V PENDANTS

SPECIFICATIONS:

DESCRIPTION

Camino is a timeless open cylinder of handcrafted European glass, that demonstrates contemporary sensibilities.

LAMPING

Standard: 40W B10 Candelabra base (E12) Incandescent 120V, or 50W Xenon, lamp not included. Dimmable with standard incandescent dimmer (not included). **Halogen:** 40W G9 Low-pressure Halogen 120V, included. Lamp is suitable for use in an open fixture, dimmable.

LED: 5W Replaceable source, 120V, dimmable, 90+ CRI, 3000°K CCT, 500 lumens, 25,000 hours. Lamp included. (Additional Color Temperatures available, including 3500°K and 4000°K)

DIFFUSER

Shade shall be handcrafted glass of various decors. 2.5" Dia. x 10" H **Opening sizes:** 33mm min. (top), 53mm min. (bottom), 3x6mm holes.

SUSPENSION

Cord-hung: 10' SVT-type cord, complete with 5" decorative sleeve at the socketholder. Jacket coordinates with metal finish. Plated stamped steel construction. Black, Bronze or Satin Nickel. See next page for mulit light options.


Stem-mount: Includes 4 connectable stem sections (3", 6", 12" and 18" lengths) plus telescoping piece for up to 3" adjustment, 10' max. 5" Dia. canopy (with swivel) and stem sections are plated steel. Black, Bronze or Satin Nickel. *Additional Stem Sections can be ordered under accessories.

MOUNTING

Installs directly to a 4" octagonal ceiling box. Suitable for sloped ceilings.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only). Consult factory concerning lower wattage labeling for energy requirements.





CAMINO SHOWN IN RUBY MATTE (5674RM) & OPAL MATTE (567407) WITH BLACK CORDSET



Project In	formation:
------------	------------

For ordering information, see next page

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 7/22




ORDERING:

CONNECTION	- SHADE OPTIONS -		- LAMP OPTIONS -		- METAL FINISH -		- OPTIONS	
Cord Fixture	567407	Opal Matte	(blank)	40W B10 Cand	BK	Black	ī	15' cord
1BC 1 Lt. Dome	567419	Carrera	HAL	40W G9 Hal	BR	Bronze	LW	Low
1BT 1 Lt. Flat	567480	Amber Matte	LED*	5W LED,	SN	Satin Nickel		wattage
	5674CM	Cobalt Blue Matte		dimmable				labeling
Stem Fixture	5674RM	Ruby Matte						_
1TT 1 Lt. Flat		*CCT options available (contact factory)						

Multi light Cord Fixture

B For Multi light Canopy




Ex. 1BT-5674RM-SN

Camino Pendant w/ Ruby Matte Glass, Satin Nickel Finish. Flat Canopy

PENDANT OPTIONS:

1BT / 1BC / B CORD-HUNG PENDANT



- Flat (1BT) or Dome (1BC) Canopy styles. Dome style allows adjustment without cutting cord.
- "B" option is pendant less canopy for multiport canopy (options to the right)
- Suitable for sloped ceilings
- Cord: 10' SVT, 5" sleeve at socketholder
- Also available in 15
- · Black, Bronze or Satin Nickel
- · Cord Sleeves are available in 18" lengths

1TT STEM PENDANT



- Swivel at canopy, suitable for sloped ceilings
- Includes telescoping section plus 4 connectable stem sections, (1x 3", 1x 6", 1x 12", 1x 18"), 10' max
- · Black, Bronze or Satin Nickel
- · Additional Stem Sections can be ordered under Accessories

ACCESSORIES:

ADDITIONAL STEM SECTIONS:

Additional connecting stems are available to increase overall length of a Stem Pendant, up to 10' max. Telescoping adjustable section allows up to 3" movement.

T20A-SN, BK or BR Adi. Section T203-SN, BK or BR 3" Section T206-SN, BK or BR 6" Section T212-SN, BK or BR 12" Section T218-SN, BK or BR 18" Section

LONGER CORD LENGTHS:

Longer cord length of 15' available. Add an " \boldsymbol{L} " to the end of the item number, i.e. 1JC-169707-SN-L.

LOW WATTAGE LABELING:

Incandescent fixture supplied with 16 watt relamp label.

Add an "LW" to the end of the item number, i.e. 1JC-169707-SN-LW.

CORD SLEEVES:

If concealing the cord is desired on a Cord-hung Pendant, order our 0.25" dia. metal sleeves. Each sleeve is 18" long and may be field cut.

T118-BK Black T118-BR Bronze T118-SN Satin Nickel

STEMHOOKS:

Suspension hooks allow cord drops to be placed wherever desired. Suitable for sloped ceilings or for greater multilight spacing

T103BK Black T103BR Bronze T103SN Satin Nickel


MULTIPORT CANOPY OPTIONS FOR CORD PENDANTS

T33X 3 LIGHT ROUND CANOPY



- Suitable for sloped ceilings
- · Black, Bronze or Satin Nickel
- 10" Dia. shades MAX, with staggered heights
- * For larger diameter glasses, Stemhooks are required for spacing

T33XL 3 LIGHT LARGE ROUND CANOPY




- Suitable for sloped ceilings
- · Black, Bronze or Satin Nickel
- · 16" Dia. shades MAX, with staggered heights
- For larger diameter glasses, Stemhooks are required for spacing

T36X 6 LIGHT ROUND CANOPY

1.25" ceilings \bigcirc

- Suitable for sloped
- Black, Bronze or Satin Nickel
- 10" Dia. shades MAX, with staggered heights
- * For larger diameter glasses, Stemhooks are required for

T39X 9 LIGHT ROUND CANOPY




- Suitable for sloped ceilings
- Black, Bronze or Satin Nickel
- 10" Dia. shades MAX, with staggered heights
- * For larger diameter glasses, Stemhooks are required for spacing

T33V 3 LIGHT BAR CANOPY




- · Suitable for sloped ceilings
- · Black, Bronze or Satin Nickel
- 20" Dia. shades MAX, with staggered heights
- * For larger diameter glasses, Stemhooks are required for spacing

T34V 4 LIGHT BAR CANOPY



- · Suitable for sloped ceilings
- · Black, Bronze or Satin Nickel
- 20" Dia. shades MAX, with staggered heights
- * For larger diameter glasses, Stemhooks are required for spacing

T37V 7 LIGHT BAR CANOPY



- · Suitable for sloped ceilings
- Black, Bronze or Satin Nickel
- 20" Dia. shades MAX, with staggered heights
- * For larger diameter glasses, Stemhooks are required for spacing

HOW TO ORDER A MULTILIGHT FIXTURE

Order your canopy with the selected 120V multi light pendants (indicated by "B" or "J" prefix) for the complete fixture:

Example: 1x T33X-SN (3 Light Round Canopy)

1x B-567418-SN (Camino Pendant in Amber Cloud)

1x B-5674CE-SN (Camino Pendant in Ceylon)

1x B-5674HN-SN (Camino Pendant in Honey)