

GEO 9 / 11

FLUSH MOUNT CEILING

location:

SPECIFICATIONS:

DESCRIPTION

Flush-mounted round ceiling luminaires, featuring handcrafted glass. Two sizes available.

LAMPING

Standard: 60W A19 120V incandescent, lamp not included. Dimmable with standard incandescent dimmer (not included).

LED: 10W Integrated source, 120V, CL dimmable, 90+ CRI, 3000°K CCT, 750 lumens, 30,000 hours, included. (For Geo 9 only)

LED: 17W Integrated source, 120V, CL dimmable, 90+ CRI, 3000°K CCT, 1200 lumens, 30,000 hours, included. (For Geo 11 only)

DIFFUSER

Handcrafted glass diffuser is available in Opal Matte decor.

Geo 9 #888407: 9" L x 9" W x 3.75" H Geo 11 #888307: 11" L x 11" W x 4.25" H

CONSTRUCTION

Glass diffuser is secured to fitter with three set screws. Stamped aluminum fitter is powder coated white.

MOUNTING


Installs directly to a 4" octagonal outlet box, centered on fixture. 90°C supply wire required for incandescent lamping.

LABELS


UL or ETL Listed. Suitable for Damp Locations (interior use only).



GEO CEILING SHOWN IN OPAL MATTE



DECOR -	- LAMP OPTIONS		- OPTIONS	
888407C 9.0" Sq. Opal Matte	(blank)	1x 60W A19 Incan	LW	Low
	LED	10W LED,		Wattage
		750 lumens		labeling



Ex. 888407C Geo 9 Ceiling w/ Opal Matte Glass

Project Information:								

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 12/18