

AERO 16 / 21

WALL SCONCES



DESCRIPTION

Wall-mounted ADA-compliant sconces featuring open-ended handcrafted glass.

LAMPING

Standard: 60W A15 120V incandescent, suitable for dimming, lamp not included. (*Incandescent dimmer is suitable for dimming, not included*) **LED:** 5W LED Replaceable source 120V, CL dimmable, 90+ CRI, 3000°K CCT, 550 lumens, 30,000 hours, lamp included.

DIFFUSER

Diffuser shall be handcrafted glass of various decors. Aero 16: $4.5''\,W\times15.5''\,H\times4''\,D$ Aero 21: $4.5''\,W\times21.25''\,H\times4''\,D$

CONSTRUCTION

Steel fitter and canopy-cover available with plated finishes. Glass is secured by steel set screws.

MOUNTING

Installs directly to a 4" octagonal outlet box, centered on fixture. 75°C supply wire required for incandescent lamping. Orient horizontal or vertical, wall-mount only.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).




For ordering information, see next page

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.






ORDERING:



FIXTURE/DECOR	- LAMP OPTIONS	- METAL FINISH	- OPTIONS
272807 Opal Matte	(blank) 2x 60W A15 Incan	BR Bronze	LW Low Wattage
2728ST Stucco	LED 1x 5W LED 120V	PN Polished Nickel	labeling
		SN Satin Nickel	

Aero 21: #2729



FIXTURE/DECOR	- LAMP OPTIONS	- METAL FINISH	- OPTIONS
272907 Opal Matte 27295T Stucco	(blank) 3x 60W A15 Incan LED 2x 5W LED 120V	BR Bronze PN Polished Nickel SN Satin Nickel	LW Low Wattage labeling

Ex. 2728ST-SN Aero 16 Wall Sconce w/ Stucco Glass, Satin Nickel Finish

Project Informat	tion:		