

MIA

VANITIES WALL

location:

SPECIFICATIONS:

DESCRIPTION

2-4 light vanity luminaires featuring handcrafted glass.

LAMPING

Standard: 40W Low-pressure G9 Halogen, 120V, lamp included. Suitable for use in an open fixture. Dimmable with standard incandescent dimmer (not included). **LED:** 5W Replaceable source, 120V, dimmable, 90+ CRI, 3000° K CCT, 450 lumens, 25,000 hours, lamp included.

DIFFUSER

Shade shall be handcrafted glass of various decors. 5.0" Dia. x 4.5" H, spaced 7.875" apart on center.

CONSTRUCTION

Fixture utilizes metal arm assembly and stamped steel body, with plated finish. Decorative finials can be removed for downlighting applications. Decorative outlet box cover optional when not required.

METAL FINISH

Fixture shall be finished in Bronze, Chrome or Satin Nickel.

MOUNTING

Installs directly to a 4" octagonal outlet box, with 1.75" left or right offset. Canopy allows direct wiring without outlet box, where armored cable or non-metallic sheathed cable is employed, and the decorative outlet box cover is not required. Orient upward or downward, wall-mount only.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



MIA SHOWN IN OPAL MATTE (177907) IN BRONZE FINISH

177919 CARRERA	1779MG MARBLE GRIGIO	1779HN HONEY	177918 AMBER CLOUD	
1779MA MAGMA	177941 GARNET	177986 BLUE CLOUD	1779HB HABANERO	

For ordering information, see next page

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 8/21

ORDERING:

FIXTURE -	GLASS OPTIONS	- METAL FINISH	- METAL FINISH -	• OPTIONS
2SW 2 Light Vanity	177907 Opal Matte	(blank) 40W G9 Hal	BR Bronze	SQ Square
3SW 3 Light Vanity	177918 Amber Clou	d LED 5W LED 120V,	CR Chrome	Canopy
4SW 4 Light Vanity	177919 Carrera	dimmable	SN Satin Nickel	
	177941 Garnet			
	177986 Blue Cloud			
	1779HB Habanero			
	1779HN Honey			
	1779MA Magma			
	1779MG Marble Grig	io		



Ex. 3SW-177907-SN

Mia 3-Light Vanity w/ Opal Matte Glass, Satin Nickel Finish







4SW: 30.375"L



Canopy allows direct wiring without outlet box, where armored cable or non-metallic sheathed cable is employed, and the decorative outlet box cover is not required. Orient upward or downward, wall-mount only.

Project Information: