



DIVI

VANITIES WALL



SPECIFICATIONS:

DESCRIPTION

2-4 light vanity luminaires featuring handcrafted glass.

LAMPING

Standard: 40W Low-pressure G9 Halogen, 120V, lamp included. Suitable for use in an open fixture. Dimmable with standard incandescent dimmer (not included).

LED: 5W Replaceable source, 120V, dimmable, 90+ CRI, 3000° K CCT, 450 lumens, 25,000 hours, lamp included.

DIFFUSER

Shade shall be handcrafted glass of various decors.

Diameter of 3.375" and height of 2.625", spaced 7.875" apart on center.

CONSTRUCTION

Fixture utilizes metal arm assembly and stamped steel body, with plated finish.

Decorative finials can be removed for downlighting applications. Decorative outlet box cover optional when not required.

METAL FINISH

Fixture shall be finished in Bronze, Chrome or Satin Nickel.

MOUNTING

Installs directly to a 4" octagonal outlet box, with 1.75" left or right offset. Canopy allows direct wiring without outlet box, where armored cable or non-metallic sheathed cable is employed, and the decorative outlet box cover is not required. Orient upward or downward, wall-mount only.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



DIVI SHOWN IN SILVER DICRO WAVY (1858SW)

185807
OPAL MATTE



1758CF
COPPER FOIL



1758GF
GOLD FOIL



1758SF
SILVER FOIL



1858VB
BLACK DICRO VINE



For ordering information, see next page


All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 6/23



ORDERING:

FIXTURE	GLASS OPTIONS	METAL FINISH	METAL FINISH	OPTIONS
2SW 2 Light Vanity	1758CF Copper Foil	(blank) 40W G9 Hal	BR Bronze	SQ Square
3SW 3 Light Vanity	1758GF Gold Foil	LED 5W LED 120V, dimmable	CR Chrome	Canopy
4SW 4 Light Vanity	1758SF Silver Foil		SN Satin Nickel	
	185807 Opal Matte			
	1858DW Black Dicro Wavy			
	1858VB Black Dicro Vine			



Ex. 3SW-1858DW-SN
 Divi 3-Light Vanity w/ Black Dicro Wavy Glass,
 Satin Nickel Finish

2SW: 14.625" L



3SW: 22.5" L



4SW: 30.375" L



Canopy allows direct wiring without outlet box, where armored cable or non-metallic sheathed cable is employed, and the decorative outlet box cover is not required. Orient upward or downward, wall-mount only.

Project Information: