

GEO 9 / 11

FLUSH MOUNT CEILING

location:

SPECIFICATIONS:

DESCRIPTION

Flush-mounted round ceiling luminaires, featuring handcrafted glass. Two sizes available.

LAMPING

Standard: 60W MAX E26 base A19, 120V, lamp not included. Dimmable with standard incandescent dimmer (not included). LED: 15W Integrated source, 120V, CL dimmable, 90+ CRI, 3000°K CCT, 1500 lumens, 50,000 hours, included. (For Geo 9 only) LED: 20W Integrated source, 120V, CL dimmable, 90+ CRI, 3000°K CCT, 2000 lumens, 50,000 hours, included. (For Geo 11 only)

DIFFUSER

Handcrafted glass diffuser is available in Opal Matte decor. Geo 9 #888407: 9" L x 9" W x 3.75" H Geo 11 #888307: 11" L x 11" W x 4.25" H

CONSTRUCTION

Glass diffuser is secured to fitter with three set screws. Stamped aluminum fitter is powder coated white.

MOUNTING

Installs directly to a 4" octagonal outlet box, centered on fixture. 90°C supply wire required for incandescent lamping.


LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



GEO CEILING SHOWN IN OPAL MATTE

Geo 9: #888407



FIXTURE/DECOR	LAMP OPTIONS		- 0	OPTIONS	
888407C 9.0" Sq. Opal Matte	(blank)	1x 60W A19 Incan	LW	Low	
	LED	15W LED,		Wattage	
		1500 lumens		labeling	

Geo 11: #888307 11* 4.25

FIXTURE/DECOR -		LAMP OPTIONS			- 0	
	888307C 11.0" Sq. Opal Matte	(blank)	2x 60W A19 Incan		LW	
		LED	20W LED,			
			2000 lumens			

PTIONS Low Wattage

labeling

Ex. 888407C Geo 9 Ceiling w/ Opal Matte Glass Shade

Project Information:								

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.