



# KAILEE

SCONCES WALL



## SPECIFICATIONS:

### DESCRIPTION

Wall-mounted **ADA-compliant** sconce featuring open-top handcrafted glass.

### LAMPING

**Standard:** 60W E12 120V incandescent, suitable for dimming. lamp not included. *(Incandescent dimmer is suitable for dimming, not included)*

**LED:** 8W LED Replaceable source 120V, CL dimmable, 90+ CRI, 3000°K CCT, 800 lumens, 30,000 hours, lamp included.

### DIFFUSER

Diffuser shall be handcrafted glass of various decors.

### CONSTRUCTION

Glass is secured to the backplate by braided wire. Rectangular backplate (nominal 6.5" W x 4" H) shall be constructed of steel, powder-coated white.

### METAL FINISH

Decorative metal accents shall be in various finish options.

### MOUNTING


Installs directly to a 4" octagonal outlet box. 75°C supply wire required for incandescent lamping. Top of glass is approximately 3.75" above the outlet box centerline.

### LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



KAILEE SHOWN IN CARRERA (701719) & OPAL MATTE (701707)



## ORDERING:

FIXTURE/DECOR	LAMP OPTIONS	METAL FINISH	OPTIONS
701707 Opal Matte	(blank) 60W E12 Incan	BK Black	LW Low
701719 Carrera	LED 8W LED 120V, dimmable	BR Bronze PN Polished Nickel SN Satin Nickel WH White	Wattage Labeling

**Ex. 701741-SN**  
Kailee Wall Sconce w/ Garnet Glass,  
Satin Nickel Finish

Project Information:

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 12/18