

PRIDE 14 / 17

SPECIFICATIONS:

DESCRIPTION

Our Pride opal Flush mount is a low profile contemporary design, with a timeless drum shaped blown opal glass shade which can suit any classic or modern decor. Opal has a very tranquil glow that is pleasing in appearance, the smooth satin finish on the opal's outer layer is a result of an extensive etching process.

LAMPING

Pride 14: 20W integrated source, 120V, CL dimmable, 90+ CRI, 3000°K CCT, 2000 lumens, 50,000 hours, included.

Pride 17: 30W integrated source, 120V, CL dimmable, 90+ CRI, 3000°K CCT, 3000 lumens, 50,000 hours, included.

DIFFUSER

Handcrafted of glass in inner Opal Matte. Pride 14: 12.6" Dia. x 3.5" H Pride 17: 15.75" Dia. x 3.75" H

CONSTRUCTION

Glass diffuser is secured to fitter with "twist & lock" bayonet action. Stamped aluminum fitter is powder coated white.


MOUNTING

Installs directly to a 4" octagonal outlet box, centered on fixture. 90°C supply wire required for incandescent lamping.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).

Pride 14:



Project Information:		

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/24



OPAL MATTE (PRIDE1407C)