PULSE

SCONCES OUTDOOF

location:

SPECIFICATIONS:

DESCRIPTION

Experience the allure of our Pulse luminaire, which boasts a hand-painted European glass diffuser with clear top and bottom. The luminaire is skillfully crafted with a semi-translucent white finish or opaque black or bronze finish, enhancing its light output and creating a captivating glow.

LAMPING

Standard: 75W A19 120V, lamps not included.

LED: 7W Replaceable LED source, 120V, dimmable, 80+ CRI, 3000°K CCT, 800 lumens, 15,000 hours, lamp included.

DIFFUSER

Glass diffuser is molded glass in Black or Bronze finish. $6^{\prime\prime}$ W x 10.5 $^{\prime\prime}$ H x 4.75 $^{\prime\prime}$ D.

CONSTRUCTION


Stamped Stainless steel fitter. Glass is secured by stainless steel set screws.

MOUNTING

Installs directly to a 4" octagonal outlet box, centered on fixture. 75°C supply wire required for incandescent lamping.

LABELS

UL or ETL Listed. Suitable for Wet Locations. May be used in Interior or Exterior applications.







PULSE-BK

PULSE-WH White/Clear

ORDERING:

FIXTURE - LAMP OPTIONS - FINISH

PULSE Pulse (blank) 75W A19
LED 7W LED BR Bronze/Clear
WH White/Clear

Ex. PULSE-BK Pulse Sconce, Black/Clear





PULSE-BR Bronze/Clear

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 7/23