



SULU

SCONCES OUTDOOR

location:
WET

SPECIFICATIONS:

DESCRIPTION

Wall-mounted sconces featuring handcrafted glass.

LAMPING

Standard: 60W T10 Medium-based 120V incandescent, lamp not included. Dimmable with standard incandescent dimmer (not included).

Edison: 40W Edison Filament Medium-based, 120V, lamp included.

LED: 4W Replaceable 120V LED GU10, dimmable, 82+ CRI, 3000°K CCT, 240 lumens, 25,000 hours, lamp included.

LED Filament: 4W Replaceable T-shape LED Filament lamp, 120V, dimmable, 90+ CRI, 3000°K CCT, 350 lumens, 15,000 hours, lamp included.

DIFFUSER

Diffuser shall be handcrafted glass of various Bubble decors. 4.75" Dia. x 10.5" H

CONSTRUCTION


Cast Aluminum bracket powdered-coated in Black, Silver or White finish. Glass secured by set screws.

MOUNTING

Installs directly to a 4" octagonal outlet box. May be used in either upward or downward orientation in indoor applications, downward only for outdoor. 75°C supply wire required for incandescent lamping.

LABELS

UL or ETL Listed. Suitable for Wet Locations (interior or exterior use).



ORDERING:

FIXTURE/DECOR	LAMP OPTIONS	METAL FINISH
SULUAM-WALL Amber Bubble	(blank) 60 WT10 Incan	BK Black
SULUBL-WALL Blue Bubble	EDIL 4W LED Filament	SL Silver
SULUCL-WALL Clear Bubble	LED 4W LED	WH White
SULUSM-WALL Smoke Bubble		

Ex. SULUAM-WALL-BK
Sulu Sconce w/ Amber Bubble Glass,
Black Finish

Project Information:



SULU SHOWN IN AMBER BUBBLE (SULUAM) & IN CLEAR BUBBLE (SULUCL)

SULUSM
SMOKE BUBBLE

SULUBL
BLUE BUBBLE



All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 8/21