



# TOMAS

SCONCES WALL



## SPECIFICATIONS:

### DESCRIPTION

Wall-mounted **ADA-compliant** sconce featuring open-ended handcrafted glass.

### LAMPING

**Standard:** 75W E26 base A19, 120V, suitable for dimming. lamp not included. *(Incandescent dimmer is suitable for dimming, not included)*

**LED:** 8W LED Replaceable source 120V, CL dimmable, 90+ CRI, 3000°K CCT, 800 lumens, 30,000 hours, lamp included.

### DIFFUSER

Diffuser shall be handcrafted glass of various decors.

### CONSTRUCTION

Glass is secured to the backplate by braided wire. Rectangular backplate (nominal 4" W x 6.5" H) shall be constructed of steel, powder-coated white.

### METAL FINISH


Decorative metal accents shall be in various finish options.

### MOUNTING

Installs directly to a 4" octagonal outlet box. 75°C supply wire required for incandescent lamping. Top of glass is approximately 3.5" above the outlet box centerline.

### LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



TOMAS SHOWN IN AMBER MATTE (704180) & RUBY MATTE (7041RM)

704107  
OPAL MATTE

7041CM  
COBALT BLUE MATTE



## ORDERING:

FIXTURE/DECOR	LAMP OPTIONS	METAL FINISH	OPTIONS
704107 Opal Matte	(blank) 75W A19	BK Black	LW Low
704180 Amber Matte	LED 8W LED 120V,	BR Bronze	Wattage
7041CM Cobalt Blue Matte	dimmmable	PN Polished Nickel	Labeling
7041RM Ruby Matte		SN Satin Nickel	
		WH White	

**Ex. 704180-SN**  
Tomas Wall Sconce w/ Amber Matte Glass,  
Satin Nickel Finish

Project Information:

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/24