

VENUS

SEMI-FLUSH MOUNT CEILING

location:

SPECIFICATIONS:

DESCRIPTION

Semi-flush mounted ceiling luminaire, featuring corregated cardboard shade and removable white acrylic shield.

LAMPING

LED: 9W Replaceable LED source, 120V, CL dimmable, 90+ CRI, 2800°K CCT, 800 lumens, 30,000 hours. Lamp included.

DIFFUSER

Shade shall be of corregated cardboard material and includes a removable white acrylic shield. 17.75" Dia. \times 7.5" H

CONSTRUCTION


Canopy (5" dia.) is plated stamped steel. Canopy and glass retainer hardware are available in either Bronze or Satin Nickel finish.

MOUNTING

Installs directly to a 4" octagonal outlet box, centered on fixture. 90°C supply wire required for incandescent lamping.

LABELS

UL or ETL Listed. Suitable for Dry Locations (interior use only).





VENUS

ORDERING:

FIXTURE/DECOR - LAMP OPTIONS - METAL FINISH

VENUSC Venus | LED 9W LED 120V, dimmable | SN Satin Nickel

Ex. VENUSC-LED-SN

Venus Ceiling, Satin Nickel Finish

Project Information:		

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/24